

LITECRAFT®

OutLED A710



OutLED AT10

Best.-Nr.: 00184708

Optical System

Optics	changeable optics
Beam Angle	25° (15° optional)

LED Lightsources

LEDs	18x 10 W multicolour LEDs
Colours	18x red, 18x green, 18x blue, 18x amber
LED Lifetime	> 50.000 hours
Colour Mixing System	RGBA

Temperature Zones

Ambient Temperature	-20° / +35° C
Operating Temperature	max. 78° C
Cooling	convection

Controlling & Programming

Protocol	USITT DMX 512
DMX 512 Channels	1/2/3/4/8 (5 modes)
Internal Memory	audio / stand alone-programms pre-programmed colours, master-/slave
Menu Display	LCD 8 digit, 2 lines
DMX 512 Connection	XLR 5 pin

Technical Details

Mains	90-264 V 47-63 Hz
Power Consumption	0,6 A at 230 V

Housing

Material	aluminium
Colour	black (silver optional)
Protection Class	IP65

Measurements/Weight

Measurements (L x W x H)	28,7 x 21,9 x 30,8 cm
Weight	6,0 kg
Assembling	compact Y-yoke for hanging and floor standing

Special Features

- 10 W LED Chips
- original italian KHATOD lenses
- RGBA in one lens
- more wide colour range due to additional amber LED
- brilliant colour mixing
- smooth dimming
- pre-programmed colour macros
- pre-programmed chasers
- stand-alone RGBA colour setting
- hold on last memory
- easy menu structure with LC-Display
- fixture hour counter
- default set option
- power in/out

Accessory inclusive

- schuko plug & socket
- 2x 50 cm DMX cable with XLR plug
- compact Y-yoke for hanging and floor standing

LMP

Gildestraße 55 | 49477 Ibbenbüren
Tel. +49 5451 5900 800 | Fax +49 5451 5900 59
sales@lmp.de | www.lmp.de



- RGBA multicolour LEDs
- KHATOD LED-optics
- 25° lens set (15° optional)
- accessories mounting (optional)
- compact Y-yoke for hanging and floor standing



- compact and rugged designed housing
- adjustable handle
- LCD 8 digit, 2 lines
- DMX in (NEUTRIK 5 pin)
- DMX out (NEUTRIK 5 pin)
- omega bracket (optional)
- power in (schuko)
- power out (schuko)



Gildestraße 55 | 49477 Ibbenbüren
 Tel. +49 5451 5900 800 | Fax +49 5451 5900 59
 sales@lmp.de | www.lmp.de